

**IN THE CLAIMS:**

1. (currently amended): A method for merging like commands for transfers between a storage medium and memory, comprising:

accumulating a plurality of commands in a queue while a first command is being processed by the storage medium, each of the plurality of commands including a first command data block (CDB) and a first scatter gather list (SGL), the first CDB configured to identify a location of a file on the storage medium, the first SGL configured to include data pointers identifying a location of data in the memory, the plurality of commands in the queue including contiguous commands and non-contiguous commands;

examining the plurality of commands in the queue while the first command is being processed, the examining further including;

checking if any of the plurality of commands are like commands through analysis of the first CDB, each of the like commands corresponding to a file stored on a storage medium; and

determining if any of the files on the storage medium are stored contiguously with respect to one another through analysis of the first CDB;

combining the like commands corresponding to contiguous files as a combined command, wherein the combined command having a second CDB and a second SGL derived from the first CDB and the first SGL ; and

issuing the combined command to the storage medium upon completion of the processing of the first command.

2. (original): The method as recited in claim 1, wherein the storage medium is a hard drive.

3. (canceled)

4. (original): The method as recited in claim 1, further including:

providing a multithread environment, the multithread environment allowing multiple read and write commands to be processed concurrently.

5. (original): The method as recited in claim 1, wherein the combined command is transparent to the operating system.

6. (canceled):

7. (currently amended): A method for combining commands for data transfer between a drive and memory, comprising:

receiving multiple read or write commands in a queue, each read and write command includes a first command data block (CDB) and a first scatter gather list (SGL), the first CDB configured to identify a location of a file on the drive, the first SGL being configured to include data pointers identifying a location of data in the memory, the plurality of commands in the queue including contiguous commands and non-contiguous commands;

processing a first command of the multiple read or write commands;

examining the multiple read or write commands, the examining including:

identifying like commands of the multiple read or write commands through analysis of the first CDB while processing the first command, each of the like commands being associated with a file stored on the drive, and

examining one of the first CDB and the first SGL to ascertain which of the files associated with the like commands are contiguous files;

creating a combined command having a second CDB and a second SGL which are derived from the first CDB and the first SGL, the combined command being configured to consolidate the identified like commands being associated with contiguous files; and

issuing the combined command to the drive.

8. (original): The method as recited in claim 7, further including:

providing a multithread environment, the multithread environment allowing multiple read and write commands to be processed concurrently.

9. (canceled)

10. (original): The method as recited in claim 7, wherein the queue has a capacity of 256 commands.

11. (original): The method as recited in claim 7, further including:

processing the combined command; and

generating one interrupt for the processed combined command.

12. (currently amended): An apparatus for merging like commands,  
comprising;

an operating system, the operating system generating read and write  
commands;

a storage media, the storage media being configured to process read and  
write commands, the read and write commands being associated with files stored on  
the storage media, each read and write command is associated with a first command  
data block (CDB) and a first scatter gather list (SGL), the first CDB being  
configured to identify the location of corresponding files on the storage media, the  
first SGL being configured to include data pointers identifying a location of data in  
the memory; and

a driver queue, the driver queue being configured to receive the read and  
write commands from the operating system, the read and write commands in the  
driver queue including contiguous commands and non-contiguous commands, the  
first CDB for the corresponding read and write commands indicating like  
commands associated with contiguous files on the storage media, the like  
commands and respective first CDB and first SGL associated with the like  
commands being consolidated into a single command having a second CDB and a  
second SGL which are derived from the first CDB and the first SGL, the single  
command being issued to the storage media.

13. (original): The apparatus of claim 12, wherein the storage media is a hard drive.

14. (original): The apparatus of claim 12, further including:

a multithread environment, the multithread environment allowing for multiple combined commands to be processed concurrently.

15. (canceled)

16. (canceled)

17. (currently amended): A computer readable media having program instructions for combining commands for data transfer between a drive and memory, comprising:

program instructions for receiving multiple read or write commands in a queue, each read and write command includes a first command data block (CDB) and a first scatter gather list (SGL), the first CDB configured to identify a location of a file on the drive, the first SGL being configured to include data pointers identifying a location of data in the memory, the read and write commands in the queue including contiguous commands and non-contiguous commands;

program instructions for processing a first command of the multiple read or write commands;

program instructions for combining multiple read or write commands, the combining including;

program instructions for identifying like commands of the multiple read or write commands through analysis of the first CDB while processing the first command, each of the like commands being associated with a file stored on the drive, and

program instructions for examining one of the first CDB and the first SGL to ascertain which of the files associated with the like commands are contiguous files;

program instructions for creating a combined command having a second CDB and a second SGL, which are derived from the first CDB and the first SGL, the combined command being configured to consolidate the identified like commands being associated with contiguous files; and

program instructions for issuing the combined command to the drive.

18. (original): The computer readable media as recited in claim 17, further including:

program instructions for providing a multithread environment.

19. (canceled)

20. (original): The computer readable media as recited in claim 17, wherein the drive is a hard drive.